


37 Conveyor / Skate Wheel

Specifications

Wheel Type:	Non-Precision
Load Capacity:	100 lbs.
Impact Rating:	200 lbs.
Body Diameter:	1-15/16"
Bore Size & Type:	5/16" – Round; Length 15/16"
Lubrication:	Oil
Ball Complement:	(8) - ¼" Diameter
Material:	Zinc Plated Steel, Hardened Sterling [®] Steel Balls & Raceways
Temperature Range:	Oil, -10 to 400 F°
Regreasable:	No – Maintenance Free
Other:	Polyurethane tires, no lube, & extreme cold oil available; contact Customer Service





Applications: Benefits & Features

Impact Rating:	FRANTZ not only tests steel conveyor wheels for cycle revolutions under load, but also performs impact testing under ANSI spec ICWM:2012 which was developed for the caster industry. Impact rating provides user confidence in applications with heavy weight or load "impact zones".
Targeted Applications:	Conveyor / skate wheels for straight or curved gravity flow conveyor applications, extendable conveyors, flow rails, wheel rails and lift gates. Used primarily in Shipping, Warehousing and Assembly.
Performance:	FRANTZ conveyor wheels undergo rigorous testing to assure years of satisfactory use. The FRANTZ Sterling [®] Steel Ball Division manufactures balls for the auto and defense industries under a Quality Management System registered to IATF 16949:2016.

...Roll Easy with FRANTZ® FRANTZ

> Customer Service, Product Samples and Quotations: 815.625.7063 FRANTZ Manufacturing Company P.O. Box 497, Sterling IL 61081-0497 www.frantz-mfg.com