

25A

Conveyor / Skate Wheel

Specifications

Wheel Type: Aluminum, Non-Precision

Load Capacity: Tortoise Shell® – 60 lbs.

Standard - Not Rated*

Body Diameter: 1-15/16"

Bore Size & Type: 5/16" - Round; Length 13/16"

Lubrication: Oil or Grease

Ball Complement: (8) - 1/4" Diameter

Material: Aluminum Shell and Washer,

Zinc Inner Race, Hardened Sterling® Steel Balls & Raceways

Temperature Oil, -10 to 400 F°


Range: Grease, -40 to 300 F°

Regreasable: No – Maintenance Free

Other: Polyurethane tires, no lube, &

extreme cold oil available; contact Customer Service





Part Number for Ordering:

Standard, Oil - 0025217023 Tortoise Shell®, Oil - 0025213023 Standard, Grs - 0025217123 Tortoise Shell®, Grs - 0025213123

Applications: Benefits & Features

Corrosion and Weight: Aluminum wheels provide added corrosion resistance when your application

demands such and minimizes wheel weight (overall conveyor weight) when

shipping considerations or light weight benefits are important.

Targeted Applications: Conveyor / skate wheels for straight or curved gravity flow conveyor

applications, extendable conveyors, flow rails, lift gates. Used primarily in

Shipping, Warehousing and Assembly.

Performance: FRANTZ conveyor wheels undergo rigorous testing to assure years of

satisfactory use. The FRANTZ Sterling® Steel Ball Division manufactures balls for the auto and defense industries under a Quality Management System registered

to IATF 16949:2016.

^{*} Standard wheel engineered the same as Tortoise Shell® wheel except the thickness of the outer shell has been reduced. By maintaining the same design and components of our Tortoise Shell® wheel, the Standard wheel outperforms other low-cost wheels based on extensive testing by FRANTZ.