

4015

GenStar® Precision Bearing

Specifications

Bearing Type: ABEC-1 Precision

Load Capacity: 300 lbs.

Mounting Type: Swage or Press Fit *

Tube Size/Gauge: 1.5" x 16g

Max OD of Body: 1.380"

Bore Size & Type: 4015: 5/16" – Round

Extension: 0.208"

Lubrication: Grease


Noise Level: Quiet


Static Discharge: Yes, Direct Injection Molded

Temperature Range: -4 to 180 Fahrenheit

Protection: Rubber Seals Front & Back

Regreasable: No – Maintenance Free





_

Applications: Benefits & Features

Dual Purpose Bearing: Great for use in either gravity or powered conveyor applications. Greased

ABEC-1 Bearing provides maintenance-free operation.

Targeted Applications: Great for use with flexible conveyors in shipping/receiving loading docks or in

production applications where flexible conveying provides value. Conveyor manufacturing, distribution/warehousing, food & beverage, air cargo/airports, manufacturing and packaging equipment. The low noise rating is a function of

polymer bushing integrated with precise rolling elements.

Can be used in high-speed Direct injection molded polymer static discharge bushing is standard and

applications: allows for excellent concentricity. Can be used in high speed powered

conveyor applications.

Long Life: The core ABEC-1 bearing is rated at 1260 lbs. The ABEC-1 high speed rating

coupled with the FRANTZ® IronGrip adapter assures long product life in many material handling and specialty equipment manufacturing applications.

^{*} Contact FRANTZ Customer Service if you have questions regarding Press Fit applications.